


Engine Model: Weichai WP10G220 Gross Power: 162kW @2200rpm

Operating Weight: 23,000kg


SR23MR SPECIFICATIONS

ENGINE			
Model		Weichai WP10G220	
Number of Cylinders		6	
Туре		4-cycle, Electronic Injection, Water-cooled	
Aspiration		Turbocharged	
Bore x Stroke		126*130mm	
Displacement		9.726L	
Gross Power		162kW @ 2200rpm	
Max. Torque		950N.m	
Rated Fuel Consumption		212g/kW.h	
Air Cleaner		2-stage, Dry Type	
POWER TRAIN			
Туре		Mechanical, All-wheel Drive	
Clutch		Dry Type	
Transmission		Electro-hydraulic Control, Power Shift Transmission	
Front Pad-drum	Width	900mm	
	Diameter	1620mm	
	Number of Teeth	40	
	Height of Teeth	160mm	
Rear Pad-drum	Width	900mm	
	Diameter	1620mm	
	Number of Teeth	40	
	Height of Teeth	160mm	
Max. Grade Ability		100%	
STEERING			
Туре		Hydraulic Power, Articulated Steering	
Front Wheel Steering Angle		±36°	
Articulation Angle		±7°	
Min. Turning Radius (Outside)		6786mm	
Min. Turning Radius (Inside)		3586mm	
BRAKES			
Service Brake		Air over Hydraulic Disc Brake, Foot Actuated	

DOZER BLADE	
Width	3200mm
Height	1678mm
Capacity	9m³
Max. Lifting Height	1050mm
Max. Cutting Depth	160mm
SPEED	
Forward,I,II,III	4.37\6.82\10km/h
Reverse,I,II	4.37\6.82km/h
CAPACITIES	
Fuel Tank	400L
Hydraulic Oil Tank	160L
Disinfectant Tank	152L
Engine Coolant	60L
ELECTRICAL SYSTEM	
Battery	2 x12V,105Ah
Alternator	28V,70A
Starter Motor	24V,7.5kW
WEIGHT	
Operating Weight	23000kg
Axle Load, Front Wheel	11500kg
Axle Load, Rear Wheel	11500kg
DIMENSIONS	
A	3200mm
В	1170mm
С	3090mm
D	455mm
E	1678mm
F	3350mm
G	7360mm
Н	3640mm



Drum Type, Manually Actuated





Parking Brake